



## KTR-550B/F

Flow Monitor Collects, Analyzes and Reports on Flow information

### FEATURE

- LCD Display
- Flow rate, totalizer
- DC 4-20 mA Output
- High · Low Contact
- Batch control
- RS-485

### APPLICATIONS

- ▶ 일반적인 적용 분야
- 유틸리티 용도: 에너지 분배로 사용되는 보조 및 공급 라인
- ▶ 화학 및 기타 공정 산업
- 응축수 과 냉각수
- 반응기에 batching과 혼합
- ▶ 기계 및 장비(OEM산업)
- 냉각재, 냉각수, 윤활유, 공기 공급
- ▶ 종이 및 펄프 산업 분야
- ▶ 철 및 금속 가공 분야

## ■ KTR-550B General Specifications

Power	AC 110/220 V (60 Hz)
Input	Multi Input
Output	Batch Contact A, B / Start, Stop, Reset, Out
Display	Flow rate, Total, Batch total
Dimension	48 mm x 96 mm x 125 mm
Material	Poly Carbonate and Aluminum
Panel cutting size	44 mm x 91 mm
Temp. range	-20 °C ~ 60 °C
Accuracy	Better than 0.1 %

## ■ KTR-550F General Specifications

Power	AC 110/220 V (60 Hz)
Input	Multi Input
Output	DC 4-20 mA
Display	Flow rate, Total
Dimension	48 mm x 96 mm 125 mm
Material	Poly Carbonate and Aluminum
Panel cutting size	44 mm x 91 mm
Temp. range	-20 °C ~ 60 °C
Accuracy	Better than 0.1 %

## ■ MODEL CODE

K T R	-	□	Specification
		550B	Batch Controller
		550F	Flow Rate, Total, DC 4-20 mA Output